



**NOTES:**

1. VIEWING ANGLE: 6:00 0' CLOCK
2. DISPLAY MODE: POSITIVE/TRANSFLECTIVE /TN TYPE
3. DRIVING VOLTAGE: 3.0V, DUTY: 1/4, BIAS: 1/3
4. OPERATING TEMP.: -20°C TO 70°C
5. STORAGE TEMP.: -25°C TO 75°C
6. CONNECTOR: PIN TYPE
7. THERE ARE MANY CROSSING IN THE VIEW

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM1	COM1				S9C	S4	S8A	S5	S10	S25	S24A	S23	S17	S7	1D	COL	2D	S6	3D	
COM2		COM2			S9A	S3	S8B	S13	2	S24B	Start	S22	S16A	S19	1A	1E	2A	2E	3A	3E
COM3			COM3		S9B	S2	S8C	S12	3	S24C	Timer	Z	S16B	AM	1B	1F	2B	2F	3B	3F
COM4				COM4	ARM	S1	S14	IG	4	S24D	Turbo	Shift	S11	PM	1G	2C	2G	3C	3G	

 **XIAMEN OCULAR LCD DEVICES CO., LTD**

6																				
5																				
4																				
3																				
2																				
1																				

VER.	MODIFY	CONTENTS	DATE	DESIGN

PART NO.	GD-4818WSP
CHECKED BY	
DESIGN BY	

COMPOSE TYPE:	DATE:	MM	DD
DATE:			

APPLICATION:	<input type="checkbox"/> Instrument <input type="checkbox"/> Automobile <input type="checkbox"/> Home Appliance <input type="checkbox"/> Air-condition <input type="checkbox"/> Other
SAMPLE:	<input type="checkbox"/> Yes <input type="checkbox"/> No