



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM	COM				1E	1D	1C	1DP	2E	2D	2C	2DP	3E	3D	3C	3DP	4E	4D	4C	4B
PIN	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
COM	4A	4F	4G	3B	3A	3F	3G	□	2B	2A	2F	2G	□	1B	1A	1F	1G	△	□	COM

NOTES:

1. VIEWING ANGLE: 6:00 O' CLOCK
2. DISPLAY MODE: POSITIVE/REFLECTIVE/TN TYPE
3. DRIVING VOLTAGE: 5.0V, STATIC
4. OPERATING TEMP.: -20° C TO 70° C
5. STORAGE TEMP.: -20° C TO 70° C
6. CONNECTOR: PIN TYPE

6																					
5																					
4																					
3																					
2																					
1																					

VER.	MODIFY	CONTENTS	DATE	DESIGN	APP	WR	DESIGN	WR	DATE	DESIGN	APP	WR
1												

XIAMEN OCULAR LCD DEVICES CO., LTD		PART NO. GD-042HWP	DESIGNER R.Y.Z 27/11-07	CHECKED BY
REVISIONS 1. 2008.08.01 2. 2008.08.01 3. 2008.08.01		APPLICATION: <input type="checkbox"/> Mobile Equipment <input type="checkbox"/> Automobile <input type="checkbox"/> Instrument <input type="checkbox"/> Other <input type="checkbox"/> New Equipment <input type="checkbox"/> After-Modification		
DRAWING TYPE: <input type="checkbox"/> New <input type="checkbox"/> Change <input type="checkbox"/> Repair		SHEET 1 OF 1		